

A & J Rental, Inc.

I have read and understand the Safety Rules and Operation Guidelines for the dunk tank I have rented. I understand that I am completely responsible for this item and the people who use the item while in my possession. I release A & J Rental, Inc. and it's employees from any and all liability from the use of this dunk tank.

Customer Print: _____

Signature: _____

A & J Rental Agent: _____

Date: _____

Easy Dunker – Dunk Tank

Towing

1. Always use a safety chains and BOTH tongue pins.
2. Check brake lights and turn signals.
3. Make sure that the target frame is folded to the side of tank and attached to cage with rubber straps. (attached to frame) Attach chain to frame and hook to cage.
4. A 2" trailer ball is required. Make sure that hitch secures snug to ball.
5. Hook safety chains to vehicle and hook up lights.
6. Target arm, target plate and balls should be stored in tow vehicle.

SET-UP

1. A level area needs to be selected for the setup location.
2. Unhook trailer, safety chains, and lights from the tow vehicle. Roll the tank to setup location.
3. Trailer tongue should be removed by taking out pins that attached tongue to trailer. Replace pins in tongue bar. (This should be stored in a safe place away from the Dunk Tank.)
4. Carefully lift tank to upright position.
5. Unhook the rubber straps and the chain from the cage and unfold the frame. The chain is now used to secure the frame to the tank unit to keep the frame from pushing forward in a wind. There is a place for a spike to be driven at the bottom of the backstop frame to keep the backstop frame secure.
6. Make sure drain plug is tight before filling with water.
7. The target arm goes behind the bar under the seat; the bolt goes into the bolthole on the frame and then goes through the hole allowed in the tarp. Once this is done the target plate is attached to the end of the target arm that has gone through the tarp hole.
8. Test the target arm by pressing on target plate. If installed correctly the seat should release. To reset the seat, pull up on the front of the seat until you hear the latch lock.

Safety Rules - Operation

1. Keep Easy Dunker – Dunk Tank away from electricity.
2. **ADULTS ONLY** to operate and supervise Dunk Tank.
3. Keep water level filled to at least 6" from top of tank.
4. Never leave a full Dunk Tank unattended by an adult.
5. When tank is unattended, always drain water.
6. Keep all non-swimmers and anyone less than 5' tall out of tank.
7. To keep from slipping, always wear tennis shoes.
8. Advise dunkee to move towards the front of the tank when coming up out of the water to avoid hitting head on the seat.
9. Only one person at a time allowed on the seat or in the tank.
10. Check that the seat is secured prior to placing full weight on seat.
11. Never stand on seat.
12. Never use baseballs or other hard balls.
13. When sitting on the seat, sit up straight, keep hands on knees, keep legs together and sit forward.
14. Never allow participant to hold on to bars/wire mesh or stick feet through bars/wire mesh.
15. Do not hit target with hands.
16. Operator only permitted behind tank or target area.
17. Person who has used drugs or consumed alcohol are NOT permitted in tank.
18. Maximum weight limit is 250 pounds.
19. Do not operate the Easy Dunker – Dunk Tank during a storm.